

如何在您的設備上 啟用eSIM



*實際顯示內容可能會根據您設備以及作業平台的不同而有所不同



掃瞄QR碼以啟用



1. 前往 [設定] 並點擊 [網路和網際網路]



2. 點擊 [SIM卡]

⊙ ♥⊿ ≌ 72%
動網路
卡,請移除裝置中的現有
G
SIM 卡嗎? ^{的號碼}

3. 點擊 [要改為下載 SIM卡嗎?]



4. 點擊 [繼續]



5. 請掃瞄我們為您寄送的 QR碼



6. 點擊 [下載]



7. 選擇您剛剛下載, 新增的 SIM卡



8. 開啟 [使用SIM卡]開關





10. 點擊 [偏好的網路類型] 並且選擇 [LTE]



手動設定 (SM-DP+)以啟用

1(3:04	Upp 27 and in
	Settings
	۹ 🖰
((:-	Connections Wi-Fi, Bluetooth, Data usage, Flight mode
()	Sounds and vibration Sound mode, Ringtone, Volume
•	Notifications Block, allow, prioritise
۰	Display Brightness, Blue light filter, Home screen
Ŧ	Wallpapers and themes Wallpapers, Themes, Icons
	Lock screen Screen lock type, Always On Display, Clock style

1. 前往 [設定] 並且點擊 [網路和網際網路]

13:04	35 th at a
< Connections	Q
Wi-Fi Connect to Wi-Fi networks.	\bigcirc
Wi-Fi Calling	\bigcirc
Bluetooth Connect to nearby Bluetooth devices.	\bigcirc
Phone visibility Allow other devices to find your phone and transfer files.	\square
NFC and payment	
Flight mode Turn off calling, messaging, and Mobile data.	Ø
Mobile networks	
Data usage	
SIM card manager	
Mobile Hotspot and Tethering	
	,



3. 點擊 [存取點名稱]



4. 點擊 [新增]

安卓 - 手動設定啟用

7,505	Y10 40 3
13:05	in it an
< Edit access point	:
Name	
Not set	
APN	
Not set	
Proxy	
Not set	
Port	
Not set	
Username	
Not set	
Password	
Not set	
Server	
Not set	
MMSC	
Not set	
MMS proxy	
Not set	
MMS port	
Not set	
	(

5. 輸入 [m-air.jp] 作為存取點名稱 及 APN

13:05	38 S al 🕯
< Edit access point	1
Name	
Not set	
APN	
Not set	
Proxy	
Not set	
Port	
Not set	
Username	
Not set	
Password	
Not set	
Server	
Not set	
MMSC	
Not set	
MMS proxy	
Not set	
MMS port	
Not set	
III O	<

6. 點擊 [右上角]

安卓 - 手動設定啟用

7:50	11. 17 BU
< Edit access point	t Save
Password	Discard
Not set	
Server	
Not set	
MMSC	
Not set	
MMS proxy	
Not set	
MMS port	
Not set	
MCC	
238	
MNC	
02	
Authentication type	
Not set	
APN type	
default	
APN protocol	
Not set	
) <

7. 點擊 [**存取**]



8. 選取 [m-air.jp]



如果正確設定後連接仍無法正常運作,請重新啟動裝置。